



PEATSA

Lauro Aguirre No.32-203 . Col. Agricultura . México, D.F. 11360
Tels: 5342-1586 . 5341-8757
contacto@peatsa.com
www.peatsa.com
Messenger: redes_peatsa@hotmail.com

BEFSX41

LINKSYS

One Solution for Internet
Sharing, VPN Capabilities, &
Enhanced Firewall Security



Instant Broadband™ EtherFast® Cable/DSL Firewall Router
with 4-Port Switch/VPN Endpoint
Model Number: BEFSX41

Benefits

- NAT and Stateful Packet Inspection Firewall to Protect Your PCs from Outside Intruders on the Internet
- Virtual Private Network (VPN) Capabilities for Secure Access of Remote Networks
- Supports Universal Plug-and-Play
- Dramatically Speed Up Your Network Gaming and Multimedia Connections
- Free Technical Support—24 Hours a Day, 7 Days a Week, Toll-Free US Calls
- 1-Year Limited Warranty

Instant Broadband™ Series

EtherFast® Cable/DSL Firewall Router with 4-Port Switch/VPN Endpoint

*Connect Your Network to the Internet and
Access a Remote Network—with Security and
Peace of Mind*

The Linksys Instant Broadband™ EtherFast® Cable/DSL Firewall Router with 4-Port Switch/VPN Endpoint is the perfect solution for connecting a small group of PCs to a high-speed broadband Internet connection or a 10/100 Ethernet backbone. The Router can be configured to limit internal users' Internet access based on URLs and/or time periods—URL filtering and time filtering. For enhanced protection against intruders from the Internet, the Router features an advanced Stateful Packet Inspection firewall.

Use the Cable/DSL Firewall Router with 4-Port Switch/VPN Endpoint to create IPSec VPN tunnels, so you can securely connect to the corporate server from your home office—or any location when you're on the road. The Router provides a dedicated port for DMZ hosting and acts as the only externally recognized Internet gateway on your local area network (LAN). With the performance and security features of the Cable/DSL Firewall Router with 4-Port Switch/VPN Endpoint, your network will take advantage of the Internet while keeping its data secure.

Features

- Protects PCs from Ping of Death, SYN Flood, Land Attacks, IP Spoofing, and Other DoS (Denial of Service) Attacks
- Supports Up to Two IPSec Virtual Private Network (VPN) Tunnels
- Supports URL Filtering and Time Filtering
- Blocks Java, ActiveX, and Cookies
- Easily Configurable through a Web Browser from Any Networked PC
- Supports IPSec and PPTP Pass-Through
- Administer and Upgrade Your Router Remotely over the Internet
- Supports Traffic and Event Logging
- Configurable as a DHCP Server on Your Network
- Administrators Can Block Specific Internal Users' Internet Access with Filtering
- Supports SNMP ver. 2.0 and SNMP MIB I and II
- Supports NTP (Network Time Protocol) for Synchronization with Real-Time Server
- Support for PPPoE Connection
- Dedicated Port for DMZ



PEATSA

Lauro Aguirre No.32-203 . Col. Agricultura . México, D.F. 11360

Tels: 5342-1586 . 5341-8757

contacto@peatsa.com

www.peatsa.com

Messenger: redes_peatsa@hotmail.com

Specifications

| | |
|---------------------|--|
| Model Number | BEFSX41 |
| Standards | IEEE 802.3, IEEE 802.3u |
| Protocol | CSMA/CD |
| Ports | WAN: One 10/100 RJ-45 Port LAN: Four 10/100 RJ-45 Ports (One with DMZ Functionality) |
| Cabling Type | UTP Category 5 or Better |
| Topology | Star |
| Speed (Mbps) | WAN: 10/100 (Half Duplex) 20/200 (Full Duplex) LAN: 10/100 (Half Duplex) 20/200 (Full Duplex) |
| LEDs | Power, Diag, DMZ WAN: Link/Act, Full/Col, 100 LAN: Link/Act, Full/Col, 100 |
| Warranty | 1-Year Limited |

Package Contents

Instant Broadband™ EtherFast® Cable/DSL Firewall Router with 4-Port Switch/VPN Endpoint

- Cable/DSL Firewall Router
- One Setup Wizard CD-ROM with User Guide Included
- One Power Adapter
- One Fast Start Guide and Registration Card

Environmental

| | |
|---------------------------|--|
| Dimensions | 7.31" x 6.16" x 1.88" (186 mm x 154 mm x 48 mm) |
| Unit Weight | 13.6 oz. (0.38 kg) |
| Power | 12V DC, 1000 mA |
| Certifications | FCC Class B, CE Mark |
| Operating Temp. | 0°C to 40°C (32°F to 104°F) |
| Storage Temp. | -20°C to 70°C (-4°F to 158°F) |
| Operating Humidity | 10% to 85% Non-Condensing |
| Storage Humidity | 5% to 90% Non-Condensing |

Linksys
17401 Armstrong Ave.
Irvine, CA 92614 USA

Sales Information (800) 546-5797

World Wide Web* <http://www.linksys.com>

Japan (03) 5259-5137

Philippines (632) 638-5580

Singapore 552-8998

Thailand 717-0770

United Kingdom 0870 7393939

*Visit our website for the most current contact information.