



# PEATSA

Lauro Aguirre No. 32-203, Col.Agricultura, México, D.F. 11360  
[www.peatsa.com](http://www.peatsa.com) Tels. 5341-8757 . 5342-1586  
contacto@peatsa.com



## 1583R

### Description:

4 Pair UTP, 200MHz Category 5e, Vertical Tray Rated, 24 AWG Solid Bare Copper, Polyolefin Insulation, PVC Jacket, Rip Cord, Sequential Marking at Two Foot Intervals

### SUITABLE APPLICATIONS:

Suitable Applications Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422

### PHYSICAL CHARACTERISTICS:

#### CONDUCTOR:

Number of Pairs 4  
Total Number of Conductors 8  
AWG 24  
Stranding Solid  
Conductor Material BC - Bare Copper

#### INSULATION:

Insulation Material PO - Polyolefin

Pair Color Code Chart :

Number	Color	Number	Color
1	White/Blue Stripe & Blue	3	White/Green Stripe & Green
2	White/Orange Stripe & Orange	4	White/Brown Stripe & Brown

### OUTER SHIELD:

Outer Shield Material Unshielded

### OUTER JACKET:

Outer Jacket Material PVC - Polyvinyl Chloride  
Outer Jacket Ripcord Yes

### OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter .195 in.

### MECHANICAL CHARACTERISTICS:

Operating Temperature Range -20°C To +75°C  
Bulk Cable Weight 29 lbs/1000 ft.  
Max. Recommended Pulling Tension 35 lbs.  
Min. Bend Radius (Install) 0.5 in.



# PEATSA

Lauro Aguirre No. 32-203 821-1 . Col. Agricultura, México, D.F. 11360  
[www.peatsa.com](http://www.peatsa.com) Tels. 5341-8757 . 5342-1586  
contacto@peatsa.com

## APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

### APPLICABLE STANDARDS:

NEC/(UL) Specification CM, UL444

CEC/C(UL) Specification CM

IEC Specification 11801 Category 5

TIA/EIA Specification 568-B.2 Category 5e

Other Specification NEMA WC-63.1 Category 5e, UL verified to Category 5e

### FLAME TEST:

UL Flame Test UL1581 Vertical Tray

CSA Flame Test FT1

### PLENUM/NON-PLENUM:

Plenum (Y/N) N

Plenum Number 1585A

### ELECTRICAL CHARACTERISTICS:

Nom. Mutual Capacitance @ 1 KHz 15 pF/ft

Maximum Capacitance Unbalance (pF/100 m) 330 pF/100 m

Nominal Velocity of Propagation 70 %

Maximum Delay (ns/100 m) 538 @ 100MHz ns/100 m

Maximum Delay Skew (ns/100m) 45 ns/100 m

Maximum Conductor DC Resistance @ 20 Deg. C 9.38 Ohms/100 m

Maximum DCR Unbalance @ 20 Deg. C 3 %

Max. Operating Voltage - UL 300 V RMS

### ELECTRICAL CHARACTERISTICS - PREMISE:

Premise Cable Electricals Table 1 :

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min. Return Loss (dB)	Min. Structural Return Loss (dB)
1	2.0	65.3	62.3	63.0	60.0	20.0	23.0
4	4.1	56.3	53.3	51.0	49.0	23.0	23.0
8	5.8	51.8	48.8	46.0	43.0	24.5	24.5
10	6.5	50.3	47.3	43.0	41.0	25.0	25.0
16	8.2	47.3	44.3	39.0	36.0	25.0	25.0
20	9.3	45.8	42.8	36.5	33.5	25.0	25.0
25	10.4	44.3	41.3	33.9	30.9	24.3	24.3
31.25	11.7	42.9	39.9	31.0	28.0	23.6	23.6
62.5	17.0	38.4	35.4	22.0	19.0	21.5	21.5
100	22.0	35.3	32.3	14.0	11.0	20.1	20.1
155	28.1	32.5	29.5	4.4	1.4	15.8	
200	32.0	30.8	27.8	4.0	1.0	15.0	



# PEATSA

Lauro Aguirre No.32-203, Col.Agricultura, México, D.F. 11360  
[www.peatsa.com](http://www.peatsa.com) Tels. 5341-8757 . 5342-1586  
[contacto@peatsa.com](mailto:contacto@peatsa.com)

Premise Cable Electricals Table 2 :

Frequency (MHz)	Input (Unfitted) Impedance (Ohms)	Fitted Impedance (Ohms)	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100±15	100±15	63.8	60.8
4	100±15	100±15	51.7	48.7
8	100±15	100±15	45.7	42.7
10	100±15	100±15	43.8	40.8
16	100±15	100±15	39.7	36.7
20	100±15	100±15	37.7	34.7
25	100±15	100±15	35.8	32.8
31.25	100±15	100±15	33.9	30.9
62.5	100±15	100±15	27.8	24.8
100	100±15	100±15	23.8	20.8
155	100±25	100±15	19.9	16.9
200	100±25	100±15	17.7	14.7

**PUT-UPS AND COLORS:**

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1583A 0021000	4 PR #24 PP FR PVC	1000	21	RED	C
1583A 002U1000	4 PR #24 PP FR PVC	U1000	21	RED	
1583A 0031000	4 PR #24 PP FR PVC	1000	21	ORANGE	C
1583A 003U1000	4 PR #24 PP FR PVC	U1000	21	ORANGE	
1583A 0041000	4 PR #24 PP FR PVC	1000	21	YELLOW	C
1583A 004U1000	4 PR #24 PP FR PVC	U1000	21	YELLOW	
1583A 0051000	4 PR #24 PP FR PVC	1000	21	GREEN, DARK	C