



PEATSA

Lauro Aguirre No. 32-203 . Col. Agricultura . México, D.F. 11360
www.peatsa.com Tels. 5342-1586 . 5341-8757
Messenger: redes_peatsa@hotmail.com
contacto@peatsa.com



CJ5E88TEI

- Exceeds TIA/EIA-568-B.2 Category 5e standard
- Forward motion termination speeds installation and places no impact on critical internal components for maximum reliability
- No punchdown tool required, optional termination tool (CGJT) ensures conductors are fully terminated
- Utilizes patented *Giga-TX™* Technology to optimize performance by reducing conductor untwist to less than 1/8"
- Terminates 4-pair 24 and 22 AWG 100 ohm solid unshielded twisted pair cable
- Can be re-terminated a minimum of 10 times
- Termination cap provides excellent strain relief, helps control cable bend radius and securely retains wires
- Termination cap includes universal label for T568A and T568B wiring schemes
- Accepts 6 and 8 position modular plugs without damage
- Red colored termination cap designates Category 5e performance with *Giga-TX™* Technology
- Can be clearly identified with optional labels and icons
- Compatible with *Mini-Com®* modular patch panels, faceplates and surface mount boxes

Part Number	CJ5E88TEI
Product Family	<i>Mini-Com® TX5e™</i> Jack Module
Part Description	Category 5e, 8 position, 8 wire universal module.
Product Type	Giga-TX Copper Module
Color	Electric Ivory
Modular Jack Type	RJ45
No. of Module Spaces	1
Performance Level	Category 5e
Wiring Scheme	T568A and T568B
UOM	PC