



PEATSA

Lauro Aguirre No. 32-203 . Col. Agricultura . México, D.F. 11360
www.peatsa.com Tels. 5342-1586 . 5341-8757
Messenger: redes_peatsa@hotmail.com
contacto@peatsa.com



CJ688TPEI

- Designed to meet TIA/EIA-568-B.2-1 Category 6 standard
- ETL tested and approved for Category 6 component compliance
- 100% tested to ensure NEXT performance
- Forward motion termination speeds installation and places no impact on critical internal components for maximum reliability
- No punchdown tool required, optional termination tool (CGJT) ensures conductors are fully terminated
- Utilizes patented *Giga-TX Technology to optimize performance by reducing conductor untwist to less than 1/8"*
- *Terminates 4-pair 24 and 22 AWG 100 ohm solid unshielded twisted pair cable*
- *Can be re-terminated a minimum of 10 times*
- Termination cap provides excellent strain relief, helps control cable bend radius and securely retains wires,
- *Termination cap is color coded for T568A and T568B wiring schemes*
- Accepts 6 and 8 position modular plugs without damage
- *Ivory colored termination cap designates Category 6 performance with Giga-TX Technology*
- *Can be clearly identified with optional labels and icons*
- *Compatible with Mini-Com modular patch panels, faceplates and surface mount boxes*

To ensure optimal performance, *PANDUIT* recommends use with other *PANDUIT*® Category 6 *PLUS* components.

Part Number	CJ688TPEI
Product Family	<i>Mini-Com</i> ® TX6 PLUS Jack Module
Part Description	Category 6, 8 position, 8 wire universal module.
Product Type	Giga-TX Copper Module
Color	Electric Ivory
No. of Module Spaces	1
Performance Level	Category 6
UOM	PC