



PEATSA

Lauro Aguirre No.32-203 . Col. Agricultura . México, D.F. 11360
Tels: 5342-1586 . 5341-8757
contacto@peatsa.com
www.peatsa.com
Messenger: redes_peatsa@hotmail.com

DP48688TG



- Exceeds TIA/EIA-568-B.2-1 Category 6 and ISO 11801 2nd Edition Class E standards
- Each port is 100% tested to ensure NEXT and return loss performance and is individually serialized to support traceability
- Utilizes 110 punchdown termination on back panel and includes retention cap for each port
- Each port contains a universal label that is color coded for T568A and T568B wiring schemes
- Angled patch panels facilitate proper bend radius control and minimize the need for horizontal cable managers
- Terminates 4 pair, 22 – 26 AWG, 100 ohm, solid or stranded twisted pair cable
- Mount to standard EIA 19" rack or 23" racks with optional extender bracket
- Write-on areas for port and panel identification available
- Can be clearly identified with labels and icons

Part Number	DP48688TG
Product Family	DP6™ PLUS Patch Panels
Part Description	48 port, Category 6, patch panel with 48 RJ45, 8 position, 8 wire ports.
Product Type	patch panel
No. of Rack Spaces	2
Performance Level	category 6
Product Category	COPPER
Product Segment	NETWORK
