



PEATSA.

Lauro Aguirre No.32-203 . Col. Agricultura. México, D.F. 11360

Tels: 5342-1586 . 5341-8757

contacto@peatsa.com

www.peatsa.com

Messenger: redes_peatsa@hotmail.com

UTP6X10BU



- Exceeds all TIA/EIA-568-B.2-AD10, ISO 11801 Class E Edition 2.1, and IEEE Std. 802.3an draft proposal channel requirements for supporting 10-GBASE-T (must be installed as part of a complete *TX6™ 10Gig™* Copper Cabling System in order to achieve 10GBASE-T certified performance)
- Each patch cord is 100% performance tested
- Constructed of *TX6™ 10Gig™* 24 AWG solid copper cable (nominal cable diameter is .275 inches) and *TX6™ PLUS* Modular Plugs for superior performance
- Plug meets all applicable FCC part 68 Subpart F requirements and exceeds IEC 60603-7 specifications
- Slender strain relief boot provides easy access in high density applications
- Plug uses an integral pair manager to optimize performance and consistency by reducing untwisting of conductors within the plug
- Plug performance in center of TIA/EIA component range, ensuring interoperability and 10 Gigabit Ethernet channel performance
- Labels on patch cords provide identification of performance level, length and quality control number
- Patented tangle free latch prevents snags and provides easy release, saving time on frequent moves, adds and changes

Part Number:	UTP6X10BU
Product Family:	<i>TX6™ 10Gig™</i> Patch Cords
RoHS Compliance Status:	RoHS compliant part number is UTP6X7BUY
Part Description:	<i>TX6™ 10Gig™</i> Category 6A patch cord.
Color:	Blue
Length (ft.):	10
Min. Order Qty.:	1
Product Type:	Copper patch cord
Std. Pkg. Qty.:	1