



# PEATSA

Lauro Aguirre No. 32-203, Col. Agricultura México, D.F. 11360  
[www.peatsa.com](http://www.peatsa.com) Tels. 5342-1586 . 5341-8757  
contacto@peatsa.com



## HLS-15R0

- HLS Strip Ties have hooks on one side and loops on the other so it adheres to itself.
- Releasable and reusable hundreds of times.
- No installation tool required.
- No risk of over tensioning and damaging high performance cabling.
- HLSP Series (Black and Maroon) are unique Hook and Loop style ties that are UL Listed (File #E56854) for use in air handling spaces per NEC Section 300-22 (C) and (D) and are UL94V-2 flame rated.
- No waste since excess can be wrapped around bundle.
- HLM Series can be used with ABMT, ABM3H, ABM4H and TMEH mounts.
- Operating temperature range: 0 to 220°F

### Note:

- Minimum 2" overlap required to achieve loop tensile rating (HLT, HLS, HLM Series) and UL Listed Rated Load (HLSP Series).

Part Number	HLS-15R0
Product Family	HLM, HLS and HLSP Strips and Rolls
Part Description	<i>Tak-Ty</i> ® Hook & Loop Cable Tie, 15' roll, .75" width, Standard, Black Can be cut to desired length, eliminating waste.
Product Type	Cable Ties
Material	Hook & Loop
Color	Black
UL Listed (File #E56854)	No
Length (In.)	180.0
Length (mm)	4,572

