



PEATSA

Lauro Aguirre No. 32-203, Col. Agricultura, México, D.F. 11360
www.peatsa.com Tels. 5342-1586 . 5341-8757
contacto@peatsa.com



HLS-15R8

- HLS Strip Ties have hooks on one side and loops on the other so it adheres to itself.
- Releasable and reusable hundreds of times.
- No installation tool required.
- No risk of over tensioning and damaging high performance cabling.
- HLSP Series (Black and Maroon) are unique Hook and Loop style ties that are UL Listed (File #E56854) for use in air handling spaces per NEC Section 300-22 (C) and (D) and are UL94V-2 flame rated.
- No waste since excess can be wrapped around bundle.
- HLM Series can be used with ABMT, ABM3H, ABM4H and TMEH mounts.
- Operating temperature range: 0 to 220°F

Note:

- Minimum 2" overlap required to achieve loop tensile rating (HLT, HLS, HLM Series) and UL Listed Rated Load (HLSP Series).

Part Number	HLS-15R8
Product Family	HLM, HLS and HLSP Strips and Rolls
Part Description	<i>Tak-Ty</i> ® Hook & Loop Cable Tie, 15' roll, .75" width, Standard, Gray
Product Type	Cable Ties
Material	Hook & Loop
Color	Gray
UL Listed (File #E56854)	No
Length (In.)	180.0
Length (mm)	4,572
Width (In.)	.750
Width (mm)	19.1
Cross Section	Standard



PEATSA

Lauro Aguirre No. 32-203, Col.Agricultura, México, D.F. 11360
www.peatsa.com Tels. 5342-1586 . 5341-8757
contacto@peatsa.com

Locking Style	Hook & Loop
Max. Bundle Dia. (mm)	Various
Max. Bundle Diameter (In.)	Various
Min. Loop Tensile Str. (N)	222
Min. Loop Tensile Strength (Lbs.)	50
Thickness (In.)	.10
Thickness (mm)	2.5
UOM	RL