



# PEATSA

lauro Aguirre No. 32-203 . Col. Agricultura, Mexico, D.F. 11360  
[www.peatsa.com](http://www.peatsa.com) Tels. 5341-8757 . 5342-1586  
contacto@peatsa.com

---



## SuperStack® 3 Switch 4250T 48-Port Plus 2 10/100/1000

### 3C17302

#### Características y ventajas

##### **Affordable, Fixed-Configuration 10/100 Switching**

For copper-wired Ethernet networks that need premium switching performance without the complexity and high price, the 3Com® SuperStack® 3 Switch 4250T is an innovative, yet eminently practical solution.

This 50-port Ethernet switch combines wirespeed Layer 2 switching with easy installation and exceptional reliability, backed by 3Com's limited lifetime warranty. Forty-eight autosensing 10/100 copper ports provide flexible desktop and workgroup attachments, while two autosensing 10/100/1000 copper uplink ports enable Gigabit Ethernet backbone and server connections.

Resiliency features such as Rapid Spanning Tree Protocol, link aggregation (for the 10/100/1000 ports), and a redundant power option help ensure uptime. Built-in Gigabit ports can be used as uplinks or for stacking with a mix of other SuperStack 3 Switch 4228G, SuperStack 3 Switch 4250T, and SuperStack 3 Switch 4226T units.

- Wirespeed, non-blocking performance

- Fixed-configuration design means the switch will operate right out of the box

- Switch can configure its own IP settings for management through SNMP, web, or CLI

- Forwarding rates up to 10.1 million packets per second

- Two built-in 10/100/1000 ports support high-speed connections as uplinks or for stacking

- Integrated stack management, for single IP management of up to four units

- Redundant power is available using 3Com SuperStack Advanced Redundant Power System

- Ships with trial version of 3Com Network Supervisor application, which configures, maps and monitors your system and provides custom alerts and reports

- Limited lifetime warranty includes fan and power supply



# PEATSA

Lauro Aguirre No. 32-203 . Col. Agricultura México, D.F. 11360  
[www.peatsa.com](http://www.peatsa.com) Tels. 5341-8757 . 5342-1586  
contacto@peatsa.com

---

## Especificaciones de producto

**Ports:** 48 autosensing 10BASE-T/100BASE-TX, two 10BASE-T/100BASE-TX/1000BASE-T

**Media Interfaces:** RJ-45

**Ethernet switching features:** Full-rate nonblocking on all Ethernet ports, full/half-duplex auto-negotiation and flow control, multicast Layer 2 filtering, 802.1Q VLAN support, 802.1p traffic prioritization, IGMP snooping

**Height:** 4.36 cm (1.7 in)

**Width:** 44.0 cm (17.3 in)

**Depth:** 27.4 cm (10.8 in)

**Weight:** 3.2 Kg (7 lb)