



PEATSA.

Lauro Aguirre No.32-203 . Col. Agricultura. México, D.F. 11360

Tels: 5342-1586 . 5341-8757

contacto@peatsa.com

www.peatsa.com

Messenger: redes_peatsa@hotmail.com

108Mbps 802.11g Wireless Access Point TEW-450APB

The TRENDnet TEW-450APB 108Mbps High Speed 802.11g Wireless Access Point with XP support, which achieves "wired" speeds wirelessly with the latest technology. Using frame bursts, frame compression, fast frames and dynamic turbo, the TEW-450APB can have speeds up to 108Mbps. The TEW-450APB is also compatible with standard 802.11b/g and has WPA-PSK, 64/128-bit WEP security.

**Note: Coverage and Speed performance might vary depending on the network environment.*



Features

- Wi-Fi Compliant with IEEE 802.11g / 802.11b Wireless Devices
- High-Speed Wireless Access Point with up to 108Mbps Connection
- Supports Access Point, AP Client, Repeater and Bridge (PTP & PTMP) Modes
- Support WDS Enable/Disable Function for AP Client & Repeater Modes
- Supports Super G and XR (eXtended Range) Technology Data Rate up to 108Mbps (In AP Mode only)
- Dynamic Data Rate Scaling at 54, 48, 36, 24, 18, 12, 9 and 6Mbps for 802.11g
- Dynamic Data Rate Scaling at 11, 5.5, 2 and 1Mbps for 802.11b
- Supports ESSID Enable/Disable to Increase Security
- Supports 64/128-bit WEP (Hex & ASCII), WPA and WPA-PSK
- Allows 802.1x and Non-802.1x Clients Running Simultaneously
- Adjust Transmit Power (Full / Half (-3dB)/ Quarter(-6dB)/ Eighth(-9dB)/ Min)
- Easy Configuration with Web Browser and Built-in Flash Memory for Firmware Upgrade
- Range for Indoor of 30 ~ 50 meters (depends on the environment)
- Range for Outdoor of 50 ~ 200 meters (without XR), 400 ~ 450 meters (with XR) (depends on the environment)
- 3-Year Warranty

Specifications

Hardware

| | |
|--------------------------|---|
| Standards | Wired: IEEE 802.3 (10Base-T), IEEE 802.3/802.3u (100Base-TX) , ANSI/IEEE 802.3 Auto Negotiation Wireless: IEEE 802.11b (11Mbps), IEEE 802.11g (54Mbps) |
| LED Indicators | Power, LAN, WLAN |
| Protocols | TCP/IP |
| Interface | LAN : 1 x 10/100Mbps Auto-MDIX Port |
| Antenna | 1 x 2dBi External Detachable Dipole Antenna (Female Reverse SMA Connector) |
| Network Protocols | 802.3u : 10/100Mbps Fast Ethernet, IP v4, UDP, ICMP, TCP, DHCP |



PEATSA.

Lauro Aguirre No.32-203 . Col. Agricultura. México, D.F. 11360

Tels: 5342-1586 . 5341-8757

contacto@peatsa.com

www.peatsa.com


Messenger: redes_peatsa@hotmail.com

| | |
|---------------------------|--|
| Power Source | 5V DC, 2A External Power Adapter |
| Dimensions (LxWxH) | 146 x 113 x 41 mm (5.7 x 4.4 x 1.6 inches) (without antenna) |
| Weight | 226g. (8 oz.) |
| Temperature | Operating: 0°~ 55°C (32°F~ 131°F) Storage: -10°~ 70°C (14°F~ 158°F) |
| Humidity | Max. 95% (non-condensing) |
| Certification | FCC, CE |

Wireless

| | |
|----------------------------------|--|
| Radio Technology | Direct Sequence Spread Spectrum (DSSS) Orthogonal Frequency Division Multiplexing (OFDM) |
| Module Technique | 802.11b: CCK, DQPSK, DBPSK 802.11g: OFDM |
| Frequency Range | 2.4 ~ 2.484 GHz |
| Transmit Power | 802.11b/g: 15±2dBm |
| Data Rate (auto fallback) | 802.11b: 11Mbps, 5.5Mbps, 2Mbps, and 1Mbps 802.11g: 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps and 6Mbps Super G: 108Mbps |
| Channels | 1~11 Channel (US) , 1~13 Channel (EU) |
| Security | 64/128-bit (WEP), WPA, WPA-PSK, ESSID Control, MAC Address Filter |
| Management | Windows Based Utility or Web Browser (HTTP) |
| Receiving Sensitivity | 11Mbps 8% PER @ -85 dBm (typical) 54Mbps 10% PER @ -70 dBm (typical) |

Networking Solution



Information provided in this document pertain to TRENDnet products and is subject to change at any time, without notice.