



PEATSA

Lauro Aguirre No. 32-203 . Col. Agricultura . México, D.F. 11360

www.peatsa.com Tels. 5342-1586 . 5341-8757

Messenger: redes_peatsa@hotmail.com

contacto@peatsa.com



107058943

110A Field-Terminated Wiring Block Kits - Category 5e/6

There are several choices in ordering the 110 Wiring Blocks:

- 110AA2, 110AB2, and 110AC2 are the Wiring Blocks with connecting blocks (A = 5-pair, B = 4-pair, and C = 3-pair), clear designation strips and blank labels.

The 110 Wiring Blocks can be used with patch cords to support Gigabit Data Rates or cross-connect wires up to 10 Mb/s. When using in patching applications, it is important to use a 110 Jumper Trough between each 100-pair block to allow for horizontal routing of patch cords.

Backboards should also be used to neatly organize the vertical routing of jumpers and patch cords.

Tech. Info & Standards:

GigaSPEED: TIA/EIA Category 6 compliant when installed with 110 GS Patch Cords

Meets UL XP7 specifications

PowerSUM: TIA/EIA Category 5e compliant when installed with PowerSUM 110 Patch Cords or cross-connect wire.

Meets UL XP6 specifications

Dimensions:

25/50 pair Height: 1.75"

100 pair Height: 3.59" (9.12cm.)

300 pair Height: 10.79" (27.41cm.)

Width: "A" block 10.72" (27.23cm.), "D" block 8.5" (21.60cm.)

Depth: "A" block 3.25" (8.25cm.), "D" block 1.4" (3.60cm.)



PEATSA

Lauro Aguirre No. 32-203 . Col. Agricultura . México, D.F. 11360

www.peatsa.com Tels. 5342-1586 . 5341-8757

Messenger: redes_peatsa@hotmail.com

contacto@peatsa.com

Fabricante	SYSTIMAX SOLUTIONS
Part Number del fabricante	110AB2-300FT
Commcode	-
Descripción	PANEL DE 300 PARES CON PATAS CON CLIPS 4 PARES Y ETIQUETAS 107058943 GS CAT6

Características	
Termination:	110
Category/Level:	CATEGORY 5
Color:	IVORY
Number of Pairs:	300
Comcode	107058943
Description	4pr clips
No.	110AB2-300FT